


ELECTRICAL CHARACTERISTICS:
 ROC=1,000 OHMS +/-0.6C
 PLATINUM THIN FILM RTD, TOLERANCE CLASS 2B
 PIN LAYOUT: (PIN 2 IS INACTIVE)



MECHANICAL CHARACTERISTICS:
 BODY: FULLY MOLDED

LEADS: SN/AG HOT SOLDER DIPPED COPPER

OPERATING TEMP RANGE: -50C TO +125C
 STORAGE TEMP RANGE: -55C TO +150C

NOTES:

	INITIAL	DATE
DRAWN		
ENG APPR.		
MAT APPR.		
Q.A. APPR.		

DIMENSIONS ARE IN INCHES
 TOLERANCES:
 FRACTIONAL $\pm 1/8$
 .X ± 0.1
 .XX ± 0.01
 .XXX ± 0.005

4/14/09	A	BC
DATE	REVISION	INITIAL



Quality Thermistor, Inc. 2108 CENTURY WAY
 BOISE, ID 83709

QTI PART NUMBER: **QT0220RTD-102B** REV **A**

SIZE **A** DWG. NO. QT0220RTD-102B

SCALE: 2:1 APPROVED FORM: QT05006-168 REV.- SHEET 1 OF 1

PROPRIETARY AND CONFIDENTIAL
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF QUALITY THERMISTOR, INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF QUALITY THERMISTOR, INC. IS PROHIBITED.